

CITY OF PERRIS

DEVELOPMENT SERVICES DEPARTMENT BUILDING AND SAFETY DIVISION

135 N. "D" Street, Perris, CA 92570-2200 **TEL: (951) 443-1029 FAX: (951) 943-3293**

Above Ground Pools 2016 California Building, Electrical & Plumbing Codes

Please submit two (3) copies of a drawing & Manufactures Specifications giving the following information:

- Label Plans, "Above Ground Pool"
- Indicate distance from property lines to pool (setbacks)
- Indicate the distance from the house and/or other structures to the proposed pool.
- Show location of pool equipment, and indicate circuit breaker size in amperes.
- Indicate if the pool is to be heated. If it is indicate the location, type and size of the proposed heating equipment and gas line.
- Indicate size and type of conduit and indicate size of conductors in conduit and show location.
- If a wood deck (over 120 square feet of surface area) is to be constructed, provide structural drawing, elevation, guard rails (if over 30 inches above the ground) and framing details,
- All 15- and 20-ampere, single-phase 125-volt receptacles located within 6.0m (20ft) of the inside walls of a pool shall be protected by a ground-fault circuit interrupter (GFCI).
- Glass (Glazing) in walls, enclosure or fences containing or facing hot tubs, spa, whirlpools, saunas, steam rooms, bathtubs, showers and indoor or outdoor swimming pools where the bottom exposed edge of the glazing is less than 60 inches (1524mm) measured vertically above any standing or walking surface shall be considered a hazardous location. This shall apply to single glazing and all panes in multiple glazing.
 - **Exception:** Glazing that is more than 60 inches (1525mm), measured horizontally and in a straight line, form the water's edge of a bathtub, hot tub, spa, whirlpool or swimming pool.
- Overhead Conductors Clearance, See 2016 California Electrical Code Table 680.8A

Please provide copies of your drawings prepared in pen or photo copies as the City does not accept pencil drawings.